

## ALBILEX<sup>®</sup>-Low Pressure Spraying Kit for the Cleaning and Disinfection of Drinking Water Tanks



The ALBILEX<sup>®</sup>-Low Pressure Spraying Kit (item-no.: 190200) consists of:

- **Low Pressure Pump**
  - o Compressed air diaphragm pump made of polypropylene (PP)
  - o Delivery pressure: max. 6 bar
  - o Pump capacity: max. 18 liters per minute
  - o Air coupling: standard rapido-type coupler NW 7.2
  - o Suction intake and pressure port: PVC-rapid assembly DN 8
  - o Suction hose
  
- **Compressor**
  - o Profimaster oil-free gas supply, type 200-25
  - o 25-liter container
  - o Pressure 8 bar
  - o 10 m pressure hose including coupling
  
- **Telescopic Spray Lance**
  - o Length: 150-450 cm, three-part (on request also lengths up to 900cm available)
  - o Completely with stop valve and nozzle
  - o 10 m hose with rapido-type coupler

In addition to ALBILEX<sup>®</sup>-Low Pressure Spraying Kit it is recommended to use a telescopic brush lance (item-no.: 190250: ≤ 4.5m, 190251: ≤ 6.0m or 190252: ≤ 9m length) with soft brush (item-no.: 190301) and nut insert V2A (Item-no.: 190308) for mechanic subsequent cleaning of the range between high and low water level.